



YachtCoatings  
**REGAFLO**  
TECHNICAL DATA SHEET

## Product description

REGAFLO is a friction-reducing additive especially conceived with fluoropolymers to be used together with any BOERO antifouling. Added to the chosen antifouling, it improves its performances in terms of fluidity. It can also be applied as an additive in the last antifouling coat.

## Product information

Finish	Tixotropic paste		
Colour	Transparent		
Solids (by volume)	ASTM D2369		25 ± 2 %
Specific gravity	UNI EN ISO 2811-1		1,24 ÷ 1,30 g/cm <sup>3</sup>
Flash point	UNI EN ISO 13736		25° C
VOC (calculated average content)	ISO 11890-2/2006		681 g/l
Packaging	0,375 Lt		

## Application and use

### INSTRUCTIONS

For one antifouling can of 0,750 Lt 125 ml.

For one antifouling can of 2,5 Lt 375 ml.

### ADDITION METHOD

Open the antifouling can and thoroughly mix until you obtain a homogenous product. Add the additive to the antifouling, according to the above mentioned proportions, pouring it slowly and constantly. Shake the antifouling, either with mechanical or manual agitation. If necessary, dilute, at this stage, the antifouling with thinner 703, considering that addition of REGAFLO improves its brushability. Apply the antifouling according to the indications of application of this product.



*YachtCoatings*  
**REGAFLOX**  
TECHNICAL DATA SHEET

## Storage

---

It is recommended to avoid exposure to air and extreme temperatures. To maximise the shelf life in the can, it is worth checking that the container is well closed during the storage and that temperature is between 5° C and 35° C. Avoid exposure to direct sunlight.

## Safety rules

---

Comply with the provisions set by the local health and safety at work regulations. Avoid the contact with the skin for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application, use appropriate protections (masks, gloves, glasses, etc). Before using, read section 7-8 of the SDS.

### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of waste disposal law, for example by taking them to the recycling centre.

Packages containing the unused products: Disposal of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling centre, recycling of packaging is prohibited in this case. Do not empty into drains or water courses. Product packaging must be kept indoor and temperature in the storage place must be between 10° C and 35 °C. Do not expose to sunlight.

## Notes

---

The values indicated in the present technical sheet can have slight variations from one batch to another. The applied product must not come in contact with water, chemicals or subjected to mechanical stress before the curing is complete. The wet film thickness refer to the non-diluted product. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experiences; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or for further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other to this one.

Rev. January 2021

2



*YachtCoatings*  
**REGAFLOX**  
TECHNICAL DATA SHEET

Rev. January 2021

3

Boero Bartolomeo S.p.A. Via Macaggi 19 - 16121 Genova, Italia - Tel. +39 010 55001 - Fax +39 010 5500.291  
[www.boeroyachtcoatings.com](http://www.boeroyachtcoatings.com) – [info@boeroyachtcoatings.com](mailto:info@boeroyachtcoatings.com)

